

Mini-Porter-Cyclone

MP-50WA CF12 Specifications

2026/08/07

Item	Contents
① Hose	Soft polyvinyl chloride (ID $\phi 38 \times 400\text{mm}$)
② Lid stopper	Stainless steel (SUS304)
③ Packing	Silicone
④ Silencer	Outer: Stainless steel (SUS304) / Inner: White cloth (PP), Glass wool
⑤ Lid stopper support	Stainless steel (SUS304)
⑥ Cyclone body	Stainless steel (SUS304) (connection: $\phi 50$/ plate thickness: 1.2mm)
⑦ Hose	Transparent PVC (ID $\phi 50 \times 3000\text{mm}$)
⑧ MP lid	Aluminum alloy casting (AC4B) with melamine resin baking finish
⑨ Draw latch	Iron (Chrome plating) Rivet (Aluminum)
⑩ Suction pipe	Aluminum (OD $\phi 50 \times 600\text{mm}$)
⑪ Tank	25L Transparent PVC
⑫ Stand	Aluminum alloy casting (AC4C) with melamine resin baking finish
⑬ Casters	Conductive casters: 4 pcs (including 1 braked caster)
⑭ Filter	Outer: Iron (Chrome plating) / Inner: Glass wool
O-ring	NBR

備考欄

